



Dual Slip On Exhaust Instructions

For Models: Wildcat 1000 (2012-2014)

Removal

- 1) Use a **Spring Puller** or a **Piece of Electrical Wire** to remove the **(4) Head Pipe-to-Silencer Springs** and remove the **Silencer**.
- 2) Remove the **Donut Gaskets** and inspect for wear or damage. Replace if necessary.

Installation



- 1) Install the supplied **Silencer Bracket** to the **Silencers**. using the supplied hardware. **Do not tighten** (See Figure #1)
- 2) Install the original or replacement **Donut Gaskets** into the **Silencer Inlets**.
- 3) Slide the **Silencers/Bracket Assembly** into the **Rubber Mounting Grommets** while carefully lining up the **Inlets** with the **Head Pipes**.

NOTE: IT MAY BE NECESSARY TO LOOSEN HEAD PIPE NUTS TO ALLOW PROPER EXHAUST SYSTEM ALIGNMENT

- 4) Use a **Spring puller** or a **Long Piece of Electrical Wire** to install (4) Supplied Springs at the **Head Pipe-to-Inlet Joints**.
- 5) Tighten all the hardware.

STOP! Inspect all the areas around the exhaust system for proper clearance and adjust if necessary.



Hardware

-  (4) 400030 - Bolt - Hex - M8-1.25 X 20
-  (1) 400084 - Bracket - Mounting - Arctic Cat®

Wildcat 1000

-  (2) 6950096 - Spark Arrester | 2 in Standard

Assembly

-  (4) 400076 - Spring(s) - Long Neck
-  (4) 400073 - Washer - Flat - 1/4"

* Click thumbnails to enlarge

Figure #1



(4) Bolt - Hex - M8-1.25 X 20



(1) Bracket - Mounting - Arctic Cat® Wildcat 1000



(2) Spark Arrester | 2 in Standard Assembly



(4) Spring(s) - Long Neck



(4) Washer - Flat - 1/4"

